## Panasonic CONNECT



Windows 11 Pro Fully Rugged Laptop with 14.0"
Outdoor Display and Modular Expansion Areas...

## **TOUGHBOOK 40**

The 14.0" fully-rugged Panasonic TOUGHBOOK 40 laptop breaks new ground offering unrivaled flexibility in even the most demanding and unpredictable environments, including Defence, Mining and Utilities. It has a modular design that allows mobile workers to modify the device quickly and easily for different challenges by equipping 8 expansion areas. The powerful rugged laptop is built for use in the most extreme conditions and designed for field specialists, incorporating quick release self-encrypting secure drives and providing up to 36-hours of battery life to support mission critical operations.

## **Key Features**

Windows 11 Pro

Intel® Core™ i5-1145G7 vPro™ Processor (optional Intel® Core™ i7-1185G7 vPro™\*)

14.0" Active Matrix (TFT) colour LCD 1920 x 1080 (FHD) with sunlight-viewable glove-enabled touchscreen (up to  $1,200 {\rm cd/m^2}$ )

Up to 180cm drop resistance\*\*\*, IP66 water and dust resistance, MIL-STD 810H certified\*\*\*

Long battery life of up to 18 hours (up to 36 hours with optional 2nd battery\*)











## TOUGHBOOK 40

https://oc.connect.panasonic.com/au/en/products/toughbook-rugged-laptops-tablets/toughbook-40

|                             | P   |
|-----------------------------|---|
|                             |   |
| Achile Commissions Diothers | Into A Care III : 114 F C 7 , Due III Due case au / antional Into A Care III : 7 , 110 F C 7 , Due III th                                     |
| Mobile Computing Platform   | Intel® Core™ i5-1145G7 vPro™ Processor (optional Intel® Core™ i7-1185G7 vPro™*) Windows 11 Pro  |
| Operating System            |   |
|                             | Built-in 16GB RAM (max 64GB RAM*)   |
| Graphic Chip                | Intel® UHD Graphics, supports Intel® Iris® Xe Graphics when 2 RAM Modules installed   |
| torage                      | Quick release 512GB NVMe OPAL SSD (with heater). Optional 2nd SSD*  |
| .CD                         | 14.0" Active Matrix (TFT) colour LCD 1920 x 1080 (FHD) LCD with sunlight-viewable glove-<br>enabled touchscreen (up to 1,200cd/m² brightness) |
| Bluetooth™                  | 5.1 Class 1   |
| Vireless LAN                | Intel® Wi-Fi6 AX201   |
| Mobile Broadband*           | 4G LTE  |
| GPS*                        | U-Blox NEO-M8J  |
| LAN                         | IEEE 802.3 10Base-T / IEEE 802.3u 100BASE-TX / IEEE 802.3ab 1000BASE-T (optional 2nd GLAN*)   |
| Sound                       | Waves MaxxAudio® Stereo Speakers  |
|                             | ·   |
|                             | 4 integrated microphones  |
| ecurity                     | TPM 2.0, Password security, Integrated hardware security lock slot  |
| ront Camera                 | 5MP with IR / privacy shutter (Windows Hello compliant) optional*   |
| JSB 3.2                     | x2 (Gen 1 Type-A)   |
| Thunderbolt 4               | x1  |
| Micro SDXC Memory Card      | x1  |
| HDMI                        | x1  |
| leadset                     | x1  |
| OC In                       | x1  |
| Port Replicator             | x1  |
| Quad Path Through Connector | x1  |
| eft Expansion Area**        | 2nd SSD,  |
|                             | Smart Card Reader,  |
|                             | DVD Multi Drive,  |
|                             | Blu Ray Drive.  |
| Right Expansion Area**      | 2nd Battery,  |
|                             | Smart Card Reader.  |

| ileauset   | A1  |
|--|---|
| DC In  | x1  |
| Port Replicator  | x1  |
| Quad Path Through Connector  | x1  |
| eft Expansion Area**   | 2nd SSD,  |
|  |   |
|  | Smart Card Reader,  |
|  | Striat Card Reduct,   |
|  |   |
|  | DVD Multi Drive,  |
|  |   |
|  | Blu Ray Drive.  |
| Right Expansion Area**   | 2nd Battery,  |
| Night Expansion Area   | Zha battery,  |
|  |   |
|  | Smart Card Reader.  |
| Rear Expansion Area**  | VGA + True Serial (RS232) + 2nd native GLAN,  |
|  |   |
|  | USB 3.1 Type A + True Serial (RS232) + 2nd HDMI,  |
|  | 03b 3.1 Type A + True Serial (N3232) + 21fd Fibility,   |
|  |   |
|  | USB 3.1 Type A + USB 3.1 Type A + 2nd HDMI.   |
| Palm Rest Expansion Area**   | Fingerprint reader (Windows Hello),   |
|  |   |
|  | Fingerprint reader (Windows Hello, Multi-user authentication),  |
|  | 5.1   |
|  |   |
|  |   |
| AC Adapter   | Contactless Smart Card Reader.  |
| •  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A  |
| Battery  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A<br>Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)   |
| Battery  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A  |
| Battery  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A<br>Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)   |
| Battery  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A<br>Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)<br>Standard: approx 18 hours (Mobile Mark™ 2014),   |
| Battery<br>Battery Life  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A<br>Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)   |
| Battery<br>Battery Life<br>Power Management  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum) Standard: approx 18 hours (Mobile Mark™ 2014), With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)*   |
| Battery Battery Life Power Management Dimensions (WxHxD)   | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum) Standard: approx 18 hours (Mobile Mark™ 2014),  With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)* Standby function, ACPI BIOS  |
| Battery Battery Life Power Management Dimensions (WxHxD) Neight  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A  Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)  Standard: approx 18 hours (Mobile Mark™ 2014),  With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)*  Standby function, ACPI BIOS  354mm x 301mm x 54.4mm (without protruding parts)  |
| Battery Battery Life Power Management Dimensions (WxHxD) Weight Drop Resistance                                  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A  Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)  Standard: approx 18 hours (Mobile Mark™ 2014),  With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)*  Standby function, ACPI BIOS  354mm x 301mm x 54.4mm (without protruding parts)  Approx 3.35kg (depending on configuration)                                    |
| Battery Battery Life Power Management Dimensions (WxHxD) Weight Drop Resistance Dust Resistance Water Resistance | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A  Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)  Standard: approx 18 hours (Mobile Mark™ 2014),  With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)*  Standby function, ACPI BIOS  354mm x 301mm x 54.4mm (without protruding parts)  Approx 3.35kg (depending on configuration)  MIL-STD810H, 180cm***             |
| Battery Battery Life Power Management Dimensions (WxHxD) Weight Drop Resistance Dust Resistance Water Resistance | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A  Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)  Standard: approx 18 hours (Mobile Mark™ 2014),  With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)*  Standby function, ACPI BIOS  354mm x 301mm x 54.4mm (without protruding parts)  Approx 3.35kg (depending on configuration)  MIL-STD810H, 180cm***  IP6x       |
| Battery Battery Life Power Management Dimensions (WxHxD) Weight Drop Resistance Dust Resistance                  | Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A  Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)  Standard: approx 18 hours (Mobile Mark™ 2014),  With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)*  Standby function, ACPI BIOS  354mm x 301mm x 54.4mm (without protruding parts)  Approx 3.35kg (depending on configuration)  MIL-STD810H, 180cm***  IP6x  IPx6 |

Footnote

\*Optional

 $\hbox{\tt **One option exclusive possible in configuration port / business expansion module}\\$ 

\*\*\*\*Tested by an independent third party lab following MIL-STD810H Method 516.8 Procedure IV for transit drop test and Method 501.7 and 502.7 Procedure II for operation temperature test. May differ depending on models and options