



Media Processors Simplify Multi-Projection Workflows for Immersive Experiences

ET-FMP50

Media Processors Simplify Multi-Projection Workflows for Immersive Experiences

Key Features

Flexible Design Streamlines Installation

Simple Yet High-Precision Adjustment

Smooth and Continuous Content Playback





ET-FMP50

<https://ep-com-p-connect-oc.wd.pisceu.panasonic.eu/au/en/et-fmp50-series>

Type	Box-type
Terminals LAN	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T, NDI® compatible
Terminals Audio Out	3.5 mm stereo mini-jack
Video Format	HAP*2 / H.264, 8-bit, 3840 x 2160 pixels, 60p, YPBPR 4:2:0, 300 Mbps / H.265, 8-bit, 4096 x 4096 pixels, 60p, YPBPR 4:2:0, 300 Mbps
Storage	4 TB
Operating System	Linux®
Power Supply	AC 100–240 V, 50/60 Hz
Dimensions (W x H x D)	Approx. 210 mm x 44 mm x 295 mm (8 1/4" x 1 23/32" x 11 5/8") (Excluding feet)
Weight	Approx. 2.0 kg (4.41 lbs) (Excluding AC adapter and cord)
Operating Environment	Operating temperature: 0–40 °C (32–104 °F), operating humidity: 10–80 % (no condensation)
Note	*1 When four HDMI™ outputs are used simultaneously. *2 ET-FMP50 only. Available via a firmware update from CY2025 Q1. *3 For the ET-FMP20 (512 GB) and ET-SBFMP10 (512 GB), approximately 30 GB of the total storage space is allocated for system usage and is unavailable to the user. *4 The operating temperature range may differ according to the specific projector model paired with the ET-SBFMP10
	3840 x 2160/60p x 1 or 1920 x 1080/60p x 4*1
	AAC-LC, 16-bit, stereo
	64 W
	HDMI™ x 4, Audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz)